

Material Safety Data Sheet - MILITEC-1 GREASE

Revised 15 August 02

Section One: Chemical Product and Company Identification

Militec, Incorporated Phone: (301) 893-3910
11828 Pika Drive Fax: (301) 893-8354
Waldorf, Maryland 20602
Product Name: MILITEC-1 Grease NLGI Grade #2
Chemical Name: petroleum grease
CAS #: Mixture
Common Name: Grease

Section Two: Composition/Information on Ingredients

COMMON CHEMICAL NAME	CAS NO.,	% (by volume)
Lithium Hydroxide	1310-66-3	< 5
12-Hydroxystearic acid	106-14-9	< 15
Hydrotreated heavy naphthenic distillate	64742-52-5	< 53
Polybutene	9003-29-6	< 10
Antimony dialkyldithiocarbamate	15890-25-2	< 1
Dimethylbenzene (xylene)	1330-20-7	< 1
MILITEC-1 Synthetic Ester		< 15

Contains no other ingredients now known to be hazardous as defined by OSHA 29 CFR 1910.1000(z).

Section Three: Hazard Identification

Principle Hazards: Prolonged or repeated skin contact may cause dermatitis.

See section 11 for complete health hazard information.

Threshold Limits: The PEL (OSHA) and the TLV (ACGIH) is 5 mg/m³ as an oil mist.

Primary Routes of Exposure:

EYE: May cause eye irritation. No significant adverse effects expected.

SKIN: Repeated or prolonged contact with skin may cause irritation, which may lead to various skin disorders. Avoid prolonged skin contact.

INHALATION: No significant adverse health effects are expected to occur in short term exposure.

ORAL: Ingestion may cause nausea, diarrhea and stomach discomfort.

Section Four: First Aid Measures

ORAL: DO NOT INDUCE VOMITING. If conscious, give 2 glasses of water. Get immediate medical attention.

EYE: Flush with water for at least 15 minutes. Get medical attention if eye irritation develops or persists.

SKIN: Wash immediately with soap and water. Remove soiled clothing. Get medical attention if irritation develops. Launder contaminated clothing.

INHALATION: Remove exposed person to fresh air. If breathing is labored, administer oxygen and obtain immediate medical attention. If irritation persists or if toxic symptoms are observed, get medical attention.

Section Five: Fire Fighting Measures

FLASH POINT: >250° C (COC) >482° F. May release flammable vapors when heated above flash point.

EXTINGUISHING MEDIA: Carbon Dioxide, dry chemical, or foam. Avoid using water.

HAZARDOUS EXPOSURE: Carbon monoxide, hydrogen chloride and asphyxiants.

SPECIAL FIRE PROCEDURES: Recommend SCBA. Use water only for cooling container. Water may cause splattering, or transport the flame.

Section Six: Accidental Release Measures

Evacuate all non-essential personnel. Personal Protective Equipment must be worn, see PPE section 8 & 16. Remove sources of ignition. Prevent entry into sewers and waterways. Contain release, pick up for recycling or disposal. Residual liquid can be absorbed with inert material. Check DOT/CERCLA and other agencies for reporting requirements. Prevent contamination to soil, waterway and sewer systems.

Section Seven: Handling and Storage

HANDLING: Avoid prolonged skin contact, breathing vapors, and contaminated clothing. Use with adequate ventilation. Wear recommended protective equipment. Practice good personal hygiene after handling. Empty containers retain material residue. Do not cut, weld, braze, solder or expose containers to other ignition sources.

STORAGE: Store in closed containers of proper construction. Store away from ignition sources and in areas of good ventilation.

Section Eight: Exposure Controls – Personal Protection

EXPOSURE LIMITS: TLV = 5 mg/m³ as oil mist

VENTILATION: Use in areas of adequate ventilation

GLOVES: Nitrile or neoprene gloves are recommended.

EYE PROTECTION: Safety glasses, goggles, or face shield are recommended.

RESPIRATORY: Self contained breathing apparatus is recommended for confined space entry.

CLOTHING: Long sleeve shirt and apron when potential for skin contact. Wear neoprene or nitrile rubber boots when necessary to avoid contaminating shoes.

Section Nine: Physical and Chemical Properties

APPEARANCE: Light Brown Grease Ph: n/d

SOLUBILITY: negligible

SPECIFIC GRAVITY: .940

VAPOR DENSITY: heavier than air

VAPOR PRESSURE: <0.01mm Hg @ 20° C

BOILING POINT: >350°C

EVAPORATION POINT: less than ether

FLAMMABILITY: N/A

FLASH POINT: 250° C

ODOR: petroleum odor **VOC. %:** nil

Section Ten: Stability and Reactivity

STABILITY: Material is normally stable at ambient temperature and pressure.

CONDITIONS TO AVOID: Oxidizing agents. Do not heat above the flash point.

POLYMERIZATION: Will not occur.

DECOMPOSITION: Carbon dioxide, carbon monoxide, hydrogen chloride.

Section Eleven: Toxicological Information

ORAL TOXICITY: Swallowing material may cause irritation of the gastrointestinal lining, nausea, vomiting, diarrhea, and abdominal pain.

EYE IRRITATION: Not expected to cause eye irritation.

SKIN IRRITATION: Not expected to be a primary skin irritant. Prolonged or repetitive contact may cause irritation.

CARCINOGENIC: This material has not been identified as a carcinogen by NTP, IARC, or OSHA. PCBs not detected at or above 2 PPM threshold limit of detection.

Section Twelve: Ecological Information

This material is expected to have adverse effects on marine and plant life. Spills may contaminate drinking water.

Section Thirteen: Disposal Considerations

DISPOSAL: Consult federal, state, and local regulations regarding disposal methods. Recycle used oil. Do not contaminate used oil with solvents or other chemicals.

Section Fourteen: Transportation Information

See 49 CFR part 171.8 through 178.510

DOT HAZARD CLASS: not regulated

GUIDE NUMBER: 27

IMDG CODE: Materials classified as DOT Combustible Liquids (flash point > 141° F and < 200° F) are not regulated by DOT in containers of 110 gallons or less for domestic shipments.

DOT SHIPPING NAME: Oil, n.o.s.

UN/NA NUMBER: NA 1270

Section Fifteen: Regulatory Information

TSCA: All components of this material are on the US TSCA Inventory.

SARA 311, SARA 312, SARA 313: contains <1 % xylene & <1 % antimony compounds

CAL PROP 65: not listed, **RCRA:** not listed, **CERCLA:** listed

Section 16 Other Information

Health Fire Reactivity: PPE

NFPA CODE: Health 1, Fire 1, Reactivity 0

HMIS CODE: Health 1, Fire 1, Reactivity 0, PPE C

RECAUTIONARY LABELS: NA

This information has been compiled from sources considered to be dependable and is accurate to the best of Militec, Inc. knowledge. Militec, Inc. makes no warranty whatsoever, expressed or implied, of MERCHANTABILITY OR FITNESS FOR THE PARTICULAR PURPOSE, regarding the accuracy of such data or the results to be obtained from the use thereof. Militec, Inc. assumes no responsibility for injury to recipient or third persons, or for any damage to any property and recipient assumes all such risks.